


GAA-350-90

Especificaciones / Specification

Motor / Motor	2,5 Hp
Diámetro max. sierra / Blade saw diameter	350 mm
Velocidad sierra / Blade saw speed	3000 rpm
Diámetro del eje / Blade saw axis diameter	32 mm
Altura máx. de corte / Max. cutting height	100 mm
Recorrido alimentador / Feeder advance range	300 mm (600 doble avance) 300 mm (600 double advance)
Pisadores neumáticos / Pneumatic Clamps	6 (3 Horiz. - 3 Vert.)
Sistemas de lubricación / Lubrication systems	Neumática mediante pulverizador. Pneumatic with Spray.
Dimensiones / Dimensions	1400x850x970 mm
Peso / Weight	260 Kg
<input type="radio"/> 90°	100 mm
<input type="checkbox"/> 90°	100x100 mm
<input type="checkbox"/> 90°	170x60 mm



Tronzadora para el corte en modo automático con alimentador y doble avance.

- Ciclo automático.
- Alimentador automático de 300 mm. 600 doble avance.
- Parada de emergencia.
- Velocidad de alimentación y corte regulables.
- Selector de longitud regulable de 5 a 600 mm.
- Corte a 90°.
- Refrigeración automática aire-aceite.
- Funcionamiento semiautomático o totalmente automático.

Cutting-off machine with automatic. Oleopneumatic feeding system with two strokes by default (2 times 300 mm).

- Automatic cycle.
- Automatic feeder of 300mm. 600 double advance.
- Emergency stop.
- Adjustable cutting and feeding speeds.
- Adjustable length selector from 5 to 600 mm.
- Cut at 90°.
- Automatic air-oil coolant pump.
- Semi-automatic or automatic operation.